



MODEL	VÝŠKA (mm)	ŠÍŘKA (mm)	HLOUBKA (mm)	ROZTEČ PŘIPOJENÍ (mm)	TEPELNÝ VÝKON (W) tj(20°C)	VODNÍ OBJEM (l)	DOPORUČENÝ VÝKON PRO KOMBINOVANÉ VYTÁPĚNÍ power (W)
EC 4573	720	450	77 - 89	408	450	3,60	200
EC 6073	720	600	77 - 89	558	604	4,35	300
EC 7573	720	750	77 - 89	708	759	5,10	300
EC 4596	960	450	77 - 89	408	562	4,53	300
EC 6096	960	600	77 - 89	558	752	5,51	300
EC 7596	960	750	77 - 89	708	943	6,49	400
EC 45132	1320	450	77 - 89	408	752	6,00	400
EC 60132	1320	600	77 - 89	558	1003	7,35	500
EC 75132	1320	750	77 - 89	708	1253	8,70	600
EC 45168	1680	450	77 - 89	408	956	7,60	500
EC 60168	1680	600	77 - 89	558	1277	9,30	600
EC 75168	1680	750	77 - 89	708	1599	11,00	700
EC 45185	1840	450	77 - 89	408	1090	8,70	500
EC 60185	1840	600	77 - 89	558	1452	10,70	700
EC 75185	1840	750	77 - 89	708	1812	12,70	900